

- Blinds ensure that the detectors' detection area is adapted to the local circumstances. Sources of interference or unwanted areas can be eliminated from the area subject to motion detection. Cover blinds are already supplied as standard. Additional blinds can be ordered separately if required.

**Cover for B.E.G. motion detectors**

**LUXOMAT® Indoor 180 – Part no. 33233**



1 to mask recording below the mounting height (to prevent small animals being detected)



Indoor 180 with blind

**Arc extinction kit for B.E.G. ceiling-mounted motion detectors**

**LUXOMAT® Arc extinction kit – Part nr. 10880**



L 62 x W 39 x H 24 mm

**LUXOMAT® Mini-Arc extinction kit – Part nr. 10882**



L 50 x W 22 x H 10 mm

**SWITCHING WITH 1 OR 2-CHANNEL MOTION DETECTORS WITH SIMPLE LIGHT MEASUREMENT**

Motion detector	Page				Clip	Simple light measurement	Motion detection	Remote controllable	Range	Additional functions
Indoor 180-R (EU version)	107	–	–	92623	–	■	■	–	max. r = 10 m	Relay version with Acoustic
Indoor 180-R (UK version)	107	–	–	92610	–	■	■	–	max. r = 10 m	Relay version with Acoustic
Indoor 180-R-2D	108	–	–	92616	–	■	■	–	max. r = 10 m	Relay version with Acoustic
Indoor 180-R/2W-UK	108	–	–	92615	–	■	■	–	max. r = 10 m	Relay version with Acoustic
Indoor 180-T	107	–	–	92622	–	■	■	–	max. r = 10 m	Triac version with Acoustic
Indoor 180-SC	109	–	–	92650	–	■	■	–	max. r = 10 m	for staircase switches

**SWITCHING WITH 1 OR 2-CHANNEL MASTER WITH DAYLIGHT APPRAISAL**

Occupancy detector	Page				Clip	Daylight measurement	Motion detection	Remote controllable	Range	Additional functions
Indoor 180-M-2C	111	–	–	92136	–	■	■	■	max. r = 10 m	–

**INEXPENSIVE EXTENSION OF THE DETECTION AREA WITH SLAVE OCCUPANCY DETECTORS**

Occupancy detector	Page				Clip	Daylight measurement	Motion detection	Remote controllable	Range	Additional functions
Indoor 180-S	112	–	–	92135	–	–	■	–	max. r = 10 m	–

**11-48 V OCCUPANCY DETECTORS**

Occupancy detector	Page				Clip	Daylight measurement	Motion detection	Remote controllable	Range	Additional functions
Indoor 180-R-11-48V-3A	113	–	–	92666	–	■	■	–	max. r = 10 m	–
Indoor 180-R-11-48V-RR	113	–	–	92667	–	■	■	–	max. r = 10 m	with reed relay

**OCCUPANCY DETECTORS FOR KNX BUS FOR SWITCHING OR DIMMING**

Occupancy detector	Page				Clip	Daylight measurement	Motion detection	Remote controllable	Range	Additional functions
Indoor 180-DIM-KNX/EIB	114	–	–	92436	–	■	■	–	max. r = 10 m	for dimming

**OCCUPANCY DETECTORS FOR LON BUS**

Occupancy detector	Page				Clip	Daylight measurement	Motion detection	Remote controllable	Range	Additional functions
Indoor 180-LON	115	–	–	92663	–	■	■	■	max. r = 10 m	–

WALL SWITCHES